

RADI8

HIGH OUTPUT INFRARED BAR HEATERS

10 YEAR WARRANTY

Powerful directional infrared heating for larger rooms, commercial areas and hard-to-heat spaces.

ONE RANGE. MULTIPLE OUTPUTS & CONTROL OPTIONS.

RADI8 infrared bar heaters deliver high-output radiant warmth in a slim aluminium body. The range includes black models from 1200W to 3000W, plus selected white 1800W and 3000W models, with standard external-control or built-in thermostat + Wi-Fi configurations.

1.2-3.0KW Heating output	WALL / CEILING Adjustable mounting	BLACK / WHITE Selected finishes	WI-FI Control option
------------------------------------	--	---	--------------------------------

- 01

STANDARD
External thermostatic control
Pair with a compatible RADI8 thermostat or control system for zoned operation.
- 02

THERMOSTAT + WI-FI
App + remote control
Selected models combine built-in temperature control, Wi-Fi connectivity and remote operation.
- 03

HIGH OUTPUT
Directional radiant heat
Outputs up to 3000W for larger rooms, workshops, commercial areas and difficult-to-heat zones.



DESIGNED FOR DEMANDING SPACES

Wall or ceiling mounting allows the heater to be directed toward the occupied zone, making the range well suited to larger and more challenging spaces.

Typical applications

Workshops • Warehouses • Churches • Hospitality • Large rooms

INFRARED BAR HEATER RANGE

Technical specification

Twelve core variants across black and white finishes with standard or integrated Wi-Fi control.

MODEL / SKU	W	DIMENSIONS (MM)	CONTROL	WEIGHT	IP	SURFACE
Standard / LH12J	1200	940 x 200 x 63	External thermostat	5.65 kg	IP44	200-300 C
Wi-Fi / LH12DW	1200	940 x 200 x 63	Wi-Fi + remote	5.65 kg	IP44	200-300 C
Standard / LH18J	1800	1240 x 200 x 63	External thermostat	7.2 kg	IP44	200-300 C
Wi-Fi / LH18DW	1800	1240 x 200 x 63	Wi-Fi + remote	7.2 kg	IP44	200-300 C
Standard / LH24J	2400	1540 x 200 x 63	External thermostat	8.9 kg	IP44	200-300 C
Wi-Fi / LH24DW	2400	1540 x 200 x 63	Wi-Fi + remote	8.9 kg	IP44	200-300 C
Standard / LH30J	3000	1840 x 200 x 63	External thermostat	10.55 kg	IP44	200-300 C
Wi-Fi / LH30DW	3000	1840 x 200 x 63	Wi-Fi + remote	10.55 kg	IP44	200-300 C
White / LHW18J	1800	1050 x 220 x 80	External thermostat	7.3 kg	IP44	330-350 C
White Wi-Fi / LHW18DW	1800	1116 x 220 x 80	Wi-Fi + remote	7.4 kg	IP44	330-350 C
White / LHW30J	3000	1600 x 220 x 80	External thermostat	9.8 kg	IP44	330-350 C
White Wi-Fi / LHW30DW	3000	1666 x 220 x 80	Wi-Fi + remote	9.9 kg	IP44	330-350 C

CONSTRUCTION

Robust aluminium housing with a slim, directional bar profile designed for high-output radiant heating.

ELECTRICAL

220-240V AC / 50Hz on current published models. Circuit design and electrical connection must suit the selected heater load.

MOUNTING

Designed for wall or ceiling mounting using adjustable brackets, allowing radiant heat to be directed toward the required zone.

CONTROL

Standard models use external control. Integrated models combine a built-in thermostat, remote control and Wi-Fi app connectivity.

INSTALLATION, CARE & WARRANTY

Bar heaters have no pumps or fans. Installation must follow the supplied product instructions, minimum clearances and applicable electrical requirements. Heater output and positioning should be selected for the room heat demand and mounting conditions.

10 YEAR
WARRANTY