

RADI8

CEILING MOUNTED INFRARED PANELS

10 YEAR WARRANTY

Discreet radiant heating engineered for fixed ceiling installation in residential, commercial and specialist spaces.

ONE RANGE. THREE CONTROL OPTIONS.

RADI8 ceiling-mounted infrared panels provide a clean, low-profile heating solution without using valuable wall or floor space. The range is available in standard, built-in thermostat and built-in thermostat + Wi-Fi configurations across 400W, 660W and 860W outputs.

IP54 Splash & dust resistant	75-95°C Operating surface	220-240V 50Hz supply	CEILING Fixed installation
--	-------------------------------------	--------------------------------	--------------------------------------

01 STANDARD External thermostatic control Compatible with RADI8 wall-mounted and app-connected thermostat options.	02 BUILT-IN THERMOSTAT Remote control included Integrated digital thermostat for temperature and timer control.	03 THERMOSTAT + WI-FI Wi-Fi & remote control Integrated control with Wi-Fi connectivity for app-based operation.
--	---	--



DESIGNED FOR INTEGRATION

Suitable for suspended grid ceilings and fixed solid-ceiling installations, subject to the appropriate fixing method and electrical installation.

Typical applications

Homes • Offices • Clinics • Meeting rooms • Retail • Hospitality

CEILING PANEL RANGE

Technical specification

Nine core models across three outputs and three control configurations.

MODEL / SKU	W	DIMENSIONS (MM)	CONTROL	WEIGHT	IP	SURFACE
Standard / CP6060GT400	400	595 x 595 x 35	External thermostat	3.5 kg	IP54	75-95°C
Standard / CP10060GT660	660	1005 x 605 x 35	External thermostat	6.5 kg	IP54	75-95°C
Standard / CP12060GT860	860	1195 x 595 x 35	External thermostat	9 kg	IP54	75-95°C
Thermostat CP6060GT400-THERM	400	595 x 595 x 35	Built-in + remote	4 kg	IP54	75-95°C
Thermostat CP10060GT660-THERM	660	1005 x 605 x 35	Built-in + remote	6.7 kg	IP54	75-95°C
Thermostat CP12060GT860-THERM	860	1195 x 595 x 35	Built-in + remote	9 kg	IP54	75-95°C
Wi-Fi / CP6060GT400-WIFI	400	595 x 595 x 35	Wi-Fi + remote	4 kg	IP54	75-95°C
Wi-Fi / CP10060GT660-WIFI	660	1005 x 605 x 35	Wi-Fi + remote	6.7 kg	IP54	75-95°C
Wi-Fi / CP12060GT860-WIFI	860	1195 x 595 x 35	Wi-Fi + remote	9 kg	IP54	75-95°C

CONSTRUCTION

Premium IR ceramic-coated surface with aluminium frame.
Carbon-crystal infrared heating technology.

ELECTRICAL

220-240V AC / 50Hz. Fixed ceiling installation. Hardwired installations should be completed by a qualified electrician.

PROTECTION

IP54 rated. Overheat protection. Published quality/safety markings: UKCA, CE and RoHS; Lot 20 applies where relevant to the control configuration.

INSTALLATION

Designed for ceiling fixing. Keep a minimum 20 cm clearance from light fittings and at least 50 cm from furniture positioned in front of the heater.

INSTALLATION, CARE & WARRANTY

Ceiling panels have no pumps, fans or other complex moving components. When switched off and cool, the surface can be cleaned with a soft damp cloth. Installation must follow the supplied instructions and applicable electrical requirements.

10 YEAR
WARRANTY