RADI8

CEILING MOUNTED INFRARED PANELS

10 YEAR
WARRANTY

Discreet radiant heating engineered for fixed ceiling installation in residential, commercial and specialist spaces.

ONE RANGE. THREE CONTROL OPTIONS.

RADI8 ceiling-mounted infrared panels provide a clean, low-profile heating solution without using valuable wall or floor space. The range is available in standard, built-in thermostat and built-in thermostat + Wi-Fi configurations across 400W, 660W and 860W outputs.

IP20	130-150°C	220-240V	CEILING
Suitable for bathrooms outside zones 0, 1 and 2, away from splashes or sprays.	Operating surface	50Hz supply	Fixed installation

01

STANDARD

External thermostatic control

Compatible with RADI8 wall-mounted and app-connected thermostat options.

02

BUILT-IN THERMOSTAT

Remote control included

Integrated digital thermostat for temperature and timer control.

03

THERMOSTAT + WI-FI

Wi-Fi & remote control

Integrated control with Wi-Fi connectivity for app-based operation.



DESIGNED FOR INTEGRATION

Surface mounting: flush to suitable concrete or plasterboard ceilings. 400W / 860W: compatible grid ceilings. 660W: not standard UK grids. Recessed / grid mounting: leave 20mm of ventilated space behind the panel. Insulation must not touch or cover its back.

Typical applications

Homes • Offices • Clinics • Meeting rooms • Retail • Hospitality

CEILING PANEL RANGE

Technical specification

Nine core models across three outputs and three control configurations.

MODEL / SKU	W	DIMENSIONS (MM)	CONTROL	WEIGHT	IP	SURFACE
Standard / CP6060GT400	**400**	595 x 595 x 35	External thermostat	3.5 kg	IP20	130-150°C
Standard / CP10060GT660	**660**	1055 x 605 x 35	External thermostat	6.5 kg	IP20	130-150°C
Standard / CP12060GT860	**860**	1195 x 595 x 35	External thermostat	9 kg	IP20	130-150°C
Thermostat CP6060GT400-THERM	**400**	595 x 595 x 35	Built-in + remote	4 kg	IP20	130-150°C
Thermostat CP10060GT660-THERM	**660**	1055 x 605 x 35	Built-in + remote	6.7 kg	IP20	130-150°C
Thermostat CP12060GT860-THERM	**860**	1195 x 595 x 35	Built-in + remote	9 kg	IP20	130-150°C
Wi-Fi / CP6060GT400-WIFI	**400**	595 x 595 x 35	Wi-Fi + remote	4 kg	IP20	130-150°C
Wi-Fi / CP10060GT660-WIFI	**660**	1055 x 605 x 35	Wi-Fi + remote	6.7 kg	IP20	130-150°C
Wi-Fi / CP12060GT860-WIFI	**860**	1195 x 595 x 35	Wi-Fi + remote	9 kg	IP20	130-150°C

CONSTRUCTION

Premium IR ceramic-coated surface with aluminium frame. Carbon-crystal infrared heating technology.

ELECTRICAL

220-240V AC / 50Hz. Fixed ceiling installation. Hardwired installations should be completed by a qualified electrician.

PROTECTION

IP20 - Suitable for bathrooms outside zones 0, 1 and 2, away from splashes or sprays. Overheat protection. UKCA, CE and RoHS; Lot 20 applies where relevant to the control configuration. Hot surface: 130-150°C. Do not touch or cover during use.

INSTALLATION

Keep at least 300mm from walls, light fittings and other objects, including in front, and 500mm between heaters. Solid ceiling: flush mounting. Recessed / grid: 20mm clear, ventilated rear space; keep insulation clear. Follow the supplied installation manual.

INSTALLATION, CARE & WARRANTY

Ceiling panels have no pumps, fans or other complex moving components. Before cleaning, switch off and disconnect the supply, then allow the heater to cool. Clean with a soft, lint-free cloth lightly dampened with water. Do not spray water onto the heater. Follow the supplied manual and electrical requirements.

10 YEAR
WARRANTY