

RADI8

CIRCULAR INFRARED CEILING HEATER

**10 YEAR
WARRANTY**

2000W suspended architectural infrared heating with integrated LED lighting for large indoor spaces.

STATEMENT DESIGN. POWERFUL RADIANT HEAT.

The RADI8 circular ceiling heater combines high-output infrared heating with a distinctive suspended ring design and integrated LED lighting. Its powder-coated aluminium body creates a modern architectural feature for commercial, hospitality and premium residential interiors.

2000W

Heating output

954MM

Outer diameter

IP44

Splash resistant

~300 C

Surface temperature

01

HIGH OUTPUT

2000W radiant heating

Designed for larger rooms and open spaces, delivering silent infrared warmth directly to people and surrounding surfaces.

02

INTEGRATED LED

Heat + ambient light

A built-in LED light ring combines practical illumination with heating in one suspended architectural fitting.

03

SMART CONTROL

Thermostat control ready

Smart temperature control is supported, with heating and lighting functions designed for convenient day-to-day operation.



MADE FOR LARGE INTERIORS

Suspended ceiling mounting provides broad radiant coverage while the circular form creates a clean focal point in contemporary spaces.

Typical applications

Hospitality • Halls • Offices • Leisure • Homes

CIRCULAR INFRARED CEILING HEATER

Technical specification

Single 2000W suspended circular heater with integrated LED lighting.

MODEL / SKU	W	DIMENSIONS	CONTROL	WEIGHT	IP	SURFACE
RH2000CGH1000-L-WIFI	2000	754 / 954 mm dia.	Smart thermostat	12.5 kg	IP44	~300 C

Marketed as the 1000mm circular model; published specification lists 754mm inner diameter and 954mm outer diameter.



CONSTRUCTION

Slim powder-coated aluminium body with graphene coating. Published heating element specification: aluminium heating tube.

ELECTRICAL & CONTROL

2000W output. Designed for smart thermostat control. Integrated LED lighting can be adjusted for brightness and colour temperature.

PROTECTION

IP44 splash-resistant construction with automatic overheat protection. Published conformity markings include UKCA, CE and RoHS.

INSTALLATION

Suspended ceiling mounting only. Minimum published installation height is 2.3m. The heater must be hardwired by a qualified electrician.

INSTALLATION, CARE & WARRANTY

Install using the supplied suspended ceiling mounting system and maintain the required clearances in accordance with the installation instructions. The unit is hardwired and should be installed by a qualified electrician. Clean only when switched off and cool. The new RADI8 datasheet range carries a 10-year warranty.

10 YEAR
WARRANTY