

RADI8

FRAMED WALL INFRARED HEATING PANELS

10 YEAR WARRANTY

Slim framed infrared heating for homes, offices and commercial interiors, with standard and built-in Wi-Fi control options.

ONE RANGE. TWO CONTROL OPTIONS.

RADI8 framed infrared panels combine a slim white aluminium frame with low-profile radiant heating. The range spans 350W to 1100W standard panels, with selected 580W, 700W and 900W models also available with a built-in thermostat, remote control and Wi-Fi

350-1100W Heating output	IP54 Splash & dust protection	75-95 C Surface temperature	WI-FI Selected models
------------------------------------	---	---------------------------------------	---------------------------------

01 STANDARD External thermostatic control Standard models can be paired with a compatible RADI8 thermostat for temperature control, scheduling and zoning.	02 THERMOSTAT + WI-FI App + remote control Selected 580W, 700W and 900W models combine built-in temperature control, Wi-Fi connectivity and remote operation.	03 FLEXIBLE INSTALLATION Slim framed design Designed primarily for wall mounting, with vertical or horizontal positioning and portable feet available for compatible models.
--	---	--



DESIGNED FOR MODERN INTERIORS

The slim white aluminium frame gives the panel a clean architectural finish, while radiant infrared warmth makes it suitable for both domestic and commercial interiors.

Typical applications

Homes • Bedrooms • Offices • Hotels • Student accommodation

FRAMED INFRARED PANEL RANGE

Technical specification

Eight core variants across standard external-control and integrated thermostat + Wi-Fi configurations.

MODEL / SKU	W	DIMENSIONS (MM)	CONTROL	WEIGHT	IP	SURFACE
Standard / PH6060GT350	350	605 x 605 x 22	External thermostat	3.95 kg	IP54	75-95 C
Standard / PH9060GT580	580	905 x 605 x 22	External thermostat	5.2 kg	IP54	75-95 C
Standard / PH12060GT700	700	1205 x 605 x 22	External thermostat	6.7 kg	IP54	75-95 C
Standard / PH12075GT900	900	1205 x 755 x 22	External thermostat	7.9 kg	IP54	75-95 C
Standard / PH12090GT1100	1100	1205 x 905 x 22	External thermostat	10.3 kg	IP54	75-95 C
Wi-Fi / PH9060GT580-WIFI	580	920 x 620 x 23	Wi-Fi + remote	5.2 kg	IP54	75-95 C
Wi-Fi / PH12060GT700-WIFI	700	1205 x 605 x 22	Wi-Fi + remote	7.5 kg	IP54	75-95 C
Wi-Fi / PH12075GT900-WIFI	900	1205 x 755 x 22	Wi-Fi + remote	7.9 kg	IP54	75-95 C

CONSTRUCTION

Premium ceramic-coated aluminium surface with a slim white aluminium frame and carbon-crystal infrared heating element.

ELECTRICAL

220-240V AC / 50Hz. Standard models can be paired with an external thermostat; hardwired work should be completed by a qualified electrician.

PROTECTION

IP54 rated with overheat protection. Published conformity markings include UKCA, CE and RoHS, with Lot 20 relevant to thermostatic control.

INSTALLATION

Designed primarily for wall mounting and can be positioned vertically or horizontally. Compatible models can also use optional portable feet.

INSTALLATION, CARE & WARRANTY

Framed panels have no pumps or fans and require minimal ongoing maintenance. Install in accordance with the supplied instructions and applicable electrical requirements. Standard models may be used with a compatible external thermostat, while selected models include built-in thermostat, remote and Wi-Fi control.

10 YEAR
WARRANTY