

RADI8

GLASS INFRARED HEATING PANELS

Premium tempered-glass radiant heating in black or white for modern residential and commercial interiors.

10 YEAR WARRANTY

ONE RANGE. TWO PREMIUM FINISHES.

RADI8 glass infrared panels combine low-profile radiant heating with a premium tempered-glass front surface. Available in black or white across 320W, 450W, 580W and 700W outputs, each model can be paired with a compatible external thermostat for temperature control and

320-700W Heating output	IP54 Splash & dust protection	70-95 C Surface temperature	WALL Fixed installation
-----------------------------------	---	---------------------------------------	-----------------------------------

01 BLACK GLASS High-gloss tempered glass A bold contemporary finish available across all four outputs, from compact 320W through to 700W.	02 WHITE GLASS Clean minimalist finish The same four heating outputs in a bright white glass finish designed to integrate discreetly into modern interiors.	03 SMART CONTROL READY External thermostat control Compatible with the RADI8 Netmostat for app control, temperature setting and 7-day scheduling when hardwired.
--	--	---



PREMIUM GLASS. DISCREET RADIANT HEAT.

A slim wall-mounted infrared heater with a tempered-glass surface, combining clean architectural styling with silent radiant heating and no moving components.

Typical applications

Homes • Bathrooms • Offices • Hotels • Retail • Hallways

GLASS INFRARED PANEL RANGE

Technical specification

Eight models across four outputs and two tempered-glass finish options.

MODEL / SKU	W	DIMENSIONS (MM)	CONTROL	WEIGHT	IP	SURFACE
Black / GH6060G320B	320	600 x 600 x 12	External thermostat	8.25 kg	IP54	70-95 C
White / GH6060G320W	320	600 x 600 x 12	External thermostat	8.25 kg	IP54	70-95 C
Black / GH8060G450B	450	800 x 600 x 12	External thermostat	10.8 kg	IP54	70-95 C
White / GH8060G450W	450	800 x 600 x 12	External thermostat	10.8 kg	IP54	70-95 C
Black / GH10060G580B	580	1000 x 600 x 12	External thermostat	13.3 kg	IP54	70-95 C
White / GH10060G580W	580	1000 x 600 x 12	External thermostat	13.3 kg	IP54	70-95 C
Black / GH12060G700B	700	1200 x 600 x 12	External thermostat	15.85 kg	IP54	70-95 C
White / GH12060G700W	700	1200 x 600 x 12	External thermostat	15.85 kg	IP54	70-95 C

CONSTRUCTION

Tempered-glass front surface in black or white with carbon-crystal infrared heating technology. All models have a slim 12 mm profile.

ELECTRICAL

220-240V AC / 50Hz. Supplied with a 13A UK plug and may be hardwired via a compatible thermostat and fused spur where required.

PROTECTION

IP54 rated for splash and dust resistance with overheat protection. Published conformity markings include UKCA, CE and RoHS; Lot 20 applies when used with the relevant smart thermostat.

INSTALLATION

Designed for fixed wall mounting using the supplied brackets. Bathroom installations and hardwired thermostat connections should be completed in the correct electrical zone by a qualified electrician.

INSTALLATION, CARE & WARRANTY

Glass panels have no pumps, fans or other complex moving components and require minimal ongoing maintenance. Clean only when switched off and cool using a soft damp cloth. Installation must follow the supplied instructions and applicable electrical requirements, particularly for bathroom locations.

10 YEAR
WARRANTY