RADI8

HIGH POWER CEILING PANELS

1250W / 1900W
Radiant heating from above. Clear space below.

10 YEAR
WARRANTY

POWERFUL RADIANT WARMTH. DISCREET CEILING INSTALLATION.

RADI8 high-power ceiling panels deliver infrared warmth towards people and surrounding surfaces without fans or forced-air circulation. Two outputs support heating layouts matched to the room, with standard, remote-thermostat and Wi-Fi control versions.

1250W / 1900W	IP20	UP TO 280°C	CEILING ONLY
Heating outputs	Dry indoor locations	Heating surface	Fixed installation

01

HIGH-POWER HEATING

Aluminium heating tube

Radiant warmth from an aluminium heating surface, with silent, fan-free operation.

02

THREE CONTROL OPTIONS

Choose the matching version

Standard external control, supplied remote thermostat, or remote thermostat with Wi-Fi app control.

03

FIXED CEILING MOUNTING

Mounting brackets supplied

Two interlocking bracket halves connect the panel to suitable ceiling fixings. Professional installation required.

DESIGNED AROUND YOUR SPACE.

Ceiling installation keeps walls and floors clear. Select the output and number of panels using the room dimensions, insulation, glazing, ceiling height and calculated heat loss.

Typical applications

Domestic rooms, offices, studios and suitable commercial interiors.

Control-version availability should be checked when ordering.

HIGH POWER CEILING PANELS

Technical specification

SPECIFICATION	1250W	1900W
Standard SKU	CP6162GT1250	CP8762GT1900
Remote thermostat SKU	CP6162GT1250-THERM	CP8762GT1900-THERM
Wi-Fi thermostat SKU	CP6162GT1250-WIFI	CP8762GT1900-WIFI
Panel body (mm)	610 × 620 × 55	870 × 620 × 55
Net weight	7.8kg	10.8kg
Heating output	1250W	1900W
Supply / cable	220-240V / 50Hz; up to 1.9m	220-240V / 50Hz; up to 1.9m
Heating system	Aluminium heating tube and surface	Aluminium heating tube and surface
IP / surface temperature	IP20 / up to 280°C	IP20 / up to 280°C
Warranty	10 years	10 years

CONTROL VERSIONS

Standard: no built-in thermostat or remote; suitable external controls required for thermostatic operation. THERM: supplied wireless room thermostat. WIFI: supplied thermostat remote plus compatible Wi-Fi app. Controlled versions have a rear junction-box receiver and a 0-45°C target setting range.

ELECTRICAL CONNECTION

Supplied with a UK plug. For permanent installation, professional hardwiring to a suitable switched fused spur is recommended. A qualified electrician must select suitable wiring and protection and complete any fixed electrical connection. Do not use an extension lead.

MOUNTING & POSITIONING

Fixed ceiling mounting only. Minimum 2.3m from floor to the lowest part of the heater. Keep each side more than 300mm from adjacent walls. The supplied bracket arrangement creates a 75mm rear-to-ceiling gap. Check ceiling strength and fixing suitability against the manual.

ENVIRONMENT & SAFE USE

IP20: dry indoor locations. In bathrooms, use only a suitable dry area outside zones 0, 1 and 2, away from splashes, sprays and running water. Avoid prolonged exposure less than 1.5m from the heater; this is not a clearance for briefly passing underneath. Keep the heater uncovered.

INSTALLATION, CARE & WARRANTY

Read the supplied manual before installation and use. Isolate the supply and allow the heater to cool before cleaning. Use a soft, lightly dampened cloth; do not spray, immerse or use abrasive cleaners. Follow the supplied warranty terms.

10 YEAR
WARRANTY