

RADI8

PREMIUM WALL INFRARED PANELS

Ultra-slim frameless radiant heating designed for clean, discreet wall installation in modern interiors.

10 YEAR WARRANTY

MINIMAL DESIGN. FOUR HEATING OUTPUTS.

RADI8 Premium Wall Panels combine a super-slim frameless white finish with carbon-crystal infrared heating. Available in 350W, 450W, 580W and 700W outputs, each model can be paired with a compatible external thermostat for temperature control and scheduling.

350-700W Heating output	IP54 Splash & dust protection	75-95 C Surface temperature	WALL Fixed installation
-----------------------------------	---	---------------------------------------	-----------------------------------

01

FRAMELESS DESIGN

Super-slim white finish

A clean borderless aluminium surface designed to sit discreetly on the wall without the visual weight of a traditional radiator.

02

FOUR OUTPUTS

350W to 700W range

Four sizes provide flexible specification for bedrooms, living spaces, offices and other residential or commercial interiors.

03

SMART CONTROL READY

External thermostat control

Compatible with the RADI8 Netmostat for app control, temperature setting and 7-day scheduling when hardwired.



CLEAN LINES. DISCREET RADIANT HEAT.

A slim frameless wall-mounted infrared heater with a powder-coated aluminium surface, combining minimalist styling with silent radiant heating and no moving components.

Typical applications

Homes • Bedrooms • Offices • Hotels • Retail • Living spaces

PREMIUM WALL PANEL RANGE

Technical specification

Four core models across four outputs in a super-slim frameless white finish.

MODEL / SKU	W	DIMENSIONS (MM)	CONTROL	WEIGHT	IP	SURFACE
Frameless / FH6060G350A	350	595 x 595 x 25	External thermostat	5.65 kg	IP54	75-95 C
Frameless / FH7060G450A	450	705 x 605 x 25	External thermostat	6.35 kg	IP54	75-95 C
Frameless / FH10060G580A	580	1005 x 605 x 25	External thermostat	8.5 kg	IP54	75-95 C
Frameless / FH12060G700A	700	1195 x 595 x 25	External thermostat	10.25 kg	IP54	75-95 C

CONSTRUCTION

Powder-coated aluminium front surface with carbon-crystal infrared heating technology. All four models have a slim 25 mm profile.

ELECTRICAL

220-240V AC / 50Hz. Supplied with a 13A UK plug and may be hardwired via a compatible thermostat and fused spur where required.

PROTECTION

IP54 rated for splash and dust resistance with overheat protection. Published conformity markings include UKCA, CE and RoHS; Lot 20 applies when used with the relevant smart thermostat.

INSTALLATION

Designed for fixed wall mounting and suitable for horizontal or vertical orientation. Hardwired thermostat connections and bathroom installations should be completed by a qualified electrician.

INSTALLATION, CARE & WARRANTY

Premium wall panels have no pumps, fans or other complex moving components and require minimal ongoing maintenance. Clean only when switched off and cool using a soft damp cloth. Installation must follow the supplied instructions and applicable electrical requirements, particularly for bathroom locations.

10 YEAR
WARRANTY